



SPECIFICATIONS

1. **RATING** : 2.5W/6.3A 250VAC
10A 250VAC
2. **WITHSTAND VOLTAGE** : AC 2000V 1 Min
3. **INSULATION RESISTANCE** : MORE THAN 100MΩ
(at DC 500V)
4. **OPERATING TEMPERATURE** : -25° C TO +85° C (MAX)
5. **SAFETY** :

7A	CONNECTOR	1	Bsp1-1/2H	t=0.6	Sn-plated	Q101-07A
6B	FUSE HOLDER(SHORT)	1	Bsp1-1/2H	t=0.5	Sn-plated	Q101-06B
6A	FUSE HOLDER	1	Bsp1-1/2H	t=0.8	Sn-plated	Q101-06A
4G	TERMINAL(SHORT)	2	Bsp1-1/2H	t=0.8	Sn-plated	Q101-04G
3B	CENTER TERMINAL	1	Bsp1-1/2H	t=2.0	Ni-plated	Q101-03B
2B	EDGE TERMINAL	2	Bsp1-1/2H	t=2.0	Ni-plated	Q101-02B
1J	FUSE COVER	1	Nylon#66	94V-2		101-01J
1K	BODY	1	Nylon#66	94V-2		101-01K1