



MORSETTI EUROPLUG MASCHIO 90° PASSO 5,08 mm

Con spalle

CORPO: polyammide 6,6 verde UL94V0

PASSO: 5,08 mm

CONTATTO: ottone stagnato

PORTATA: 12A - 250V

RES. ISOLAMENTO: >5 MOHM

RIGIDITA' DIELETTRICA: 2500 V

RIGIDITA' ISOLAMENTO: A.C. 1500 V/Min.

TEMP. LAVORO: -30°C÷+120°C

PER MORSETTI: serie 5/12252

CERTIFICATO



	N° Poli	L mm	P/N Fornitore
ART. 05/12402-00	2	11,66	XY2500R-D
ART. 05/12403-00	3	16,74	XY2500R-D
ART. 05/12404-00	4	21,82	XY2500R-D
ART. 05/12405-00	5	26,90	XY2500R-D
ART. 05/12406-00	6	31,98	XY2500R-D
ART. 05/12407-00	7	37,06	XY2500R-D
ART. 05/12408-00	8	42,14	XY2500R-D
ART. 05/12409-00	9	47,22	XY2500R-D
ART. 05/12410-00	10	52,30	XY2500R-D
ART. 05/12411-00	11	57,38	XY2500R-D
ART. 05/12412-00	12	62,46	XY2500R-D