

25W Single Group Switch Power supply



Main technical parameters

Model	A richiesta	13/25400-00	A richiesta	13/25402-00
DC output voltage、current	5V 5A	12V 2.1A	15V 1.7A	24V 1.1A
Wave and noise	50mVp-p	50mVp-p	50mVp-p	75mVp-p
Inlet stability	± 0.5%	± 0.5%	± 0.5%	± 0.5%
Load stability	± 1%	± 0.5%	± 0.5%	± 0.5%
Efficiency	76%	78%	79%	81%
Adjustable range for DC voltage	± 10%	± 10%	± 10%	± 10%
AC input voltage range	85~132VAC/170~264VAC (Selected by switch) 47~63Hz, 240~370VDC			
Input Current	0.8A/110V 0.4A/220VAC			
AC inrush current	(Cold-start current) 15A/115VAC 30A/230V			
Overload protection	105%~130%(hiccup mode, auto-recovery)			
Over-voltage protection	...			
Setup rise hold up time	200ms 100ms 30ms			
Withstand voltage	I/P-O/P: 1.5KVAC, I/P-FG: 1.5KVAC, O/P-FG: 0.5KVAC 1minute			
Isolation resistance	I/P-O/P, I/P-FG, O/P-FG:500VDC/100MΩ			
Working temperature and humidity	-10°C~+60°C, 20%~90%RH			
Safety standards	(Design refer)GB4943, UL60950, EN60950			
EMC standards	(Design refer)GB9254, EN55022 (Class)B			
Dimensions	99x97x35mm			
Weight	0.3Kg			

Dimensional Drawing

- ◆ Terminal pin no. Assignment
- Pin 1: DC output +V
 - Pin 2: DC output -V
 - Pin 3: GND
 - Pin 4.5: AC input

