



Part No.:Hi-05A4SBDVC-241H23D

19/04360-00


§ Standard 5mm diameter package.

Characters

§ High intensity.

ITEM		MATERIALS
Resin(Mold)		Epoxy
Lens Color Code	C	Water Transparent
	T	Colored Transparent
	D	White Diffused
	E	Colored Diffused
Lead Frame		Ag Plating Iron Alloy
Dice		InGaN

Outline Dimensions



§ All dimensions are in millimeters (inches).


§ Tolerance is ± 0.25 (.010) mm unless otherwise noted.

Absolute Maximum Ratings (Ta=25°C)

Item	Symbol	Value	Unit
Power Dissipation	PD	120	mW
DC Forward Current	IF	30	mA
Pulsed Forward Current	IFP	100*	mA
Reverse Voltage	VR	5	V
Operating Temperature	Topr	-25 ~ +80	°C
Storage Temperature	Tstg	-40 ~ +100	°C
Soldering Temperature	Tsol	260for5secΔ	°C

* Duty 1/10 Pulse Width 0.1ms Δ At the position of 4mm from the bottom of the package

Directive Characteristics ($T_a=25^{\circ}\text{C}$)



Electrical-Optical Characteristics (Ta=25°C)

Parameter	Symbol	Value			Unit	Test condition
		Min.	Typ.	Max.		
Forward Voltage	V _f	---	3.0	3.2	V	If=20mA
Luminous intensity	I _v	6000	---	9000	mcd	If=20mA
Wavelength	λ(&λd)	---	465	470	(nm)	If=20mA
	y	---	---	---	---	If=20mA
Reverse Current	I _r	---	---	5	μA	V _r =5V
Viewing angle	2θ1/2	---	25	---	Deg	If=20mA
Spectral half bandwidth	Δλ	---	30	---	nm	If=20mA